

**No. PDL  
PETROLEUM DISCHARGE LAYFLAT HOSE**



Part Number	Inside Diameter	Outside Diameter	Weight LB/FT	Working Pressure-PSI
PDL-100	1"	1-1/4"	.14	300
PDL-150L	1-1/2"	1-11/16"	.21	150
PDL-150	1-1/2"	1-3/4"	.30	200
PDL-200L	2"	2-3/16"	.30	150
PDL-200	2"	2-1/4"	.44	250
PDL-250L	2-1/2"	2-11/16"	.42	150
PDL-300L	3"	3-3/16"	.46	150
PDL-300	3"	3-5/16"	.64	250
PDL-400L	4"	4-3/16"	.64	150
PDL-400	4"	4-3/8"	.86	250
PDL-600	6"	6-1/4"	1.42	250
PDL-800	8"	8-1/4"	2.1	200

**Recommended For:** Designed for delivery of fluids or gases, resistant to many products such as oil, grease, acids, bases, salts, sewage and seawater.

**Tube:** Black or yellow, Nitrile/PVC blend resistant to oil/weather.

**Temperature & Range:** -4°F to 176°F.

**Reinforcement:** Polyester reinforcement.

**Cover:** Ribbed, highly resistant to oil, abrasion and weathering.

**Lengths:** Standard 200 ft., and 100 ft. for 8" diameter, also cut and/or coupled to client's individual requirements.

**Couplings:** Cam and Groove and combination nipples.