

**No. RC500SJ  
SINGLE JACKET 500 PSI RUBBER FIRE HOSE**



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
RC500SJ-1550	1-1/2"	50'	500	250
RC500SJ-1575	1-1/2"	75'	500	250
RC500SJ-15100	1-1/2"	100'	500	250
RC500SJ-2050	2"	50'	500	250
RC500SJ-2075	2"	75'	500	250
RC500SJ-20100	2"	100'	500	250
RC500SJ-2550	2-1/2"	50'	500	250
RC500SJ-2575	2-1/2"	75'	500	250
RC500SJ-25100	2-1/2"	100'	500	250

Nitrile synthetic rubber provides a rugged cover for this lightweight single jacket hose designed for use in industrial and marine environments. The deep ribbed pattern offers excellent abrasion resistance and the homogeneous heavy-duty one-piece cover and liner construction resists heat and most chemicals.

**FEATURES:** Nitrile synthetic rubber one-piece cover and liner, no drying required, abrasion resistant cover, impervious to water, oil, gas and most chemicals, heat resistant (welding sparks, etc.), virtually kink resistant, meets Underwriters and Factory Mutual standards, lightweight easy to handle

**Tube/Cover:** Red Nitrile.

**Lengths:** Standard in 50, 75 and 100 ft., also cut and/or coupled to clients individual requirements.

**Couplings:** Available uncoupled and coupled in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..