

**No. WD
HEAVY DUTY WATER DISCHARGE HOSE**



Part Number	Inside Diameter	Outside Diameter	Number of Plies	Weight LB/FT	Working Pressure-PSI
WD-125	1-1/4"	1-21/32"	4	.45	200
WD-150	1-1/2"	1-57/64"	4	.59	200
WD-200	2"	2-33/64"	4	.81	150
WD-250	2-1/2"	2-61/64"	4	1.08	150
WD-300	3"	3-35/64"	4	1.25	150
WD-400	4"	4-39/64"	4	1.62	150
WD-600	6"	6-35/64"	2	3.35	150
WD-800	8"	8-15/32"	2	4.92	150
WD-1000	10"	10-5/8"	1	5.10	150
WD-1200	12"	12-9/16"	1	5.8	100

Recommended As: Heavy duty water discharge hose for tough operating conditions.

Tube: Black EPDM & SBR blend.

Reinforcement: Multiple plies of spiral high tensile cord.

Cover: Black abrasion, weather, ozone & sunlight resistant, EPDM blended rubber.

Lengths: Standard 100 ft., cut and/or coupled to client's individual specifications.

Couplings: Cam & Groove, combination nipples or pin lug short shank couplings attached with a single bolt, double bolt or band type clamps.

Also available in standard duty and heavy wall water discharge.