

**No. WSD  
WATER SUCTION HOSE**



Part Number	Inside Diameter	Outside Diameter	Bend Radius	Weight LB/FT	Working-Pressure-PSI
WSD-100	1"	1-3/8"	6"	.52	150
WSD-125	1-1/4"	1-21/32"	7"	.63	150
WSD-150	1-1/2"	1-59/64"	8"	.82	150
WSD-200	2"	2-1/2"	10"	1.15	150
WSD-250	2-1/2"	3"	15"	1.65	150
WSD-300	3"	3-1/2"	18"	2.11	150
WSD-350	3-1/2"	4"	14"	2.37	150
WSD-400	4"	4-19/32"	25"	3.05	150
WSD-500	5"	5-21/32"	29"	3.95	150
WSD-600	6"	6-45/64"	32"	4.55	150
WSD-800	8"	8-45/64"	40"	8.98	150
WSD-1000	10"	10-23/32"	50"	10.3	150
WSD-1200	12"	12-51/64"	60"	12.4	90

**Recommended As:** A general service water suction hose for use in construction, mining and agriculture.

**Tube:** Black EPDM blended rubber.

**Temperature & Range:** -40° To 185°F.

**Reinforcement:** Spiraled high tensile textile cords and double steel helix wire.

**Cover:** Black weather and ozone resistant, EPDM blended rubber.

**Lengths:** Standard 100 ft: 1" thru 6"; Standard 20 Ft: 8" thru 10", also cut and/or coupled to client's individual specifications.

**Couplings:** Cam And Groove, pin lug short shank couplings or combination nipples.