

**No. PSD
PETROLEUM SUCTION & DISCHARGE HOSE**



Part Number	Inside Diameter	Outside Diameter	Bend Radius	Weight LB/FT	Working Pressure-PSI
PSD-075	3/4"	1-1/8"	4"	.40	150
PSD-100	1"	1-7/16"	5"	.49	150
PSD-125	1-1/4"	1-21/32"	6"	.65	150
PSD-150	1-1/2"	1-57/64"	7"	.98	150
PSD-200	2"	2-7/16"	10"	1.22	150
PSD-250	2-1/2"	3"	12"	1.70	150
PSD-300	3"	3-15/32"	15"	2.03	150
PSD-400	4"	4-9/16"	20"	3.42	150
PSD-500	5"	5-21/32"	26"	5.30	150
PSD-600	6"	6-51/64"	30"	7.22	150
PSD-800	8"	8-29/32"	48"	11.90	150

Recommended For: Suction and discharge application in tank car and truck transfer of gasoline, oil and other petroleum base products.

Tube: Smooth black nitrile rubber. Resistant to up to 50% Aromatics.

Temperature & Range: -40° to 212°F.

Reinforcement: Spiraled high tensile textile cords and double steel helix wire. For static grounding - use helix wires.

Cover: Smooth, black neoprene, oil and ozone resistant.

Lengths: Standard 100 ft., also cut and/or coupled to client's individual requirements.

Couplings: Cam and Groove and combination nipples .