

**No. SS  
MARINE EXHAUST HOSE**



Part Number	ID	OD	# of plies	Wt lb/ft	WP PSI
SS-269-118	1-1/8"	1-9/16"	2	.52	200
SS-269-114	1-1/4"	1-13/16"	2	.75	200
SS-269-1516	1-5/16"	1-7/8"	2	.78	200
SS-269-138	1-3/8"	1-5/16"	2	.78	200
SS-269-112	1-1/2"	2-1/16"	2	.87	200
SS-269-158	1-5/8"	2-3/16"	2	.94	200
SS-269-134	1-3/4"	2-5/16"	2	1.02	200
SS-269-178	1-7/8"	2-7/16"	2	1.08	200
SS-269-200	2"	2-9/16"	2	1.11	200
SS-269-218	2-1/8"	2-11/16"	2	1.21	200
SS-269-214	2-1/4"	2-13/16"	2	1.26	200
SS-269-238	2-3/8"	2-15/16"	2	1.32	200
SS-269-212	2-1/2"	3-1/16"	2	1.45	200
SS-269-258	2-5/8"	3-3/16"	2	1.53	200
SS-269-234	2-3/4"	3-5/16"	2	1.58	200
SS-269-278	2-7/8"	3-7/16"	2	1.64	200
SS-269-300	3"	3-5/8"	4	1.52	200
SS-269-318	3-1/8"	3-3/4"	4	1.70	200

Part Number	ID	OD	# of plies	Wt lb/ft	WP PSI
SS-269-314	3-1/4"	3-7/8"	4	1.76	200
SS-269-312	3-1/2"	4-1/8"	4	1.78	200
SS-269-400	4"	4-5/8"	4	1.97	200
SS-269-418	4-1/8"	4-3/4"	4	1.98	200
SS-269-414	4-1/4"	4-7/8"	4	2.09	200
SS-269-412	4-1/2"	5-1/8"	4	2.22	200
SS-269-500	5"	5-15/16"	6	3.84	200
SS-269-5916	5-9/16"	6-1/2"	6	4.12	200
SS-269-600	6"	6-15/16"	6	4.65	200
SS-269-658	6-5/8"	7-9/16"	6	5.03	200
SS-269-700	7"	7-15/16"	6	5.31	200
SS-269-800	8"	8-15/16"	6	5.91	150
SS-269-858	8-5/8"	9-1/2"	6	6.94	150
SS-269-1000	10"	11"	6	7.83	150
SS-269-1034	10-3/4"	11-3/4"	6	8.40	100
SS-269-1200	12"	13"	6	9.03	100
SS-269-1234	12-3/4"	13-5/8"	6	9.46	100

**Description:** Premium grade, heavy duty marine exhaust hose. High pressure, multi-purpose product for use as a flexible connection to transfer wet exhaust. Tube resists high temperatures found in marine engine compartments. Durable cover is heat, ozone and abrasion resistant.

**Tube:** Black seamless nitrile blend.

**Temperature & Range:** -40°F to 200°F.

**Reinforcement:** Multiple plies of polyester.

**Cover:** Nitrile blend.

**Lengths:** Standard 12.5 ft., 25 ft., 50 ft., also cut and/or coupled to client's individual requirements.