

**No. NP-2
GENERAL PURPOSE DUCT**



| Part Number | Inside Diameter | Working Pressure PSI@70°F | Max. Neg. Pressure In. Hg | Tensile Strength lbs. | Crush Resistance lbs. | Weight LB/FT |
|-------------|-----------------|---------------------------|---------------------------|-----------------------|-----------------------|--------------|
| NP-2-150 | 1-1/2" | 32 | 26 | 160 | 700 | .16 |
| NP-2-200 | 2" | 30 | 24 | 200 | 500 | .22 |
| NP-2-250 | 2-1/2" | 28 | 22 | 240 | 420 | .28 |
| NP-2-300 | 3" | 25 | 20 | 290 | 390 | .33 |
| NP-2-350 | 3-1/2" | 24 | 19 | 300 | 350 | .42 |
| NP-2-400 | 4" | 23 | 18 | 310 | 320 | .48 |
| NP-2-500 | 5" | 22 | 17 | 390 | 300 | .61 |
| NP-2-600 | 6" | 21 | 16 | 420 | 290 | .70 |
| NP-2-700 | 7" | 20 | 15 | 440 | 275 | .92 |
| NP-2-800 | 8" | 19 | 14 | 450 | 260 | 1.04 |
| NP-2-1000 | 10" | 18 | 13 | 480 | 250 | 1.36 |
| NP-2-1200 | 12" | 17 | 11 | 490 | 240 | 1.85 |
| NP-2-1400 | 14" | 16 | 9 | 500 | 230 | 2.10 |
| NP-2-1600 | 16" | 15 | 7 | 510 | 220 | 2.40 |

This neoprene-coated polyester ducting is by far the most versatile of all the general-purpose wire reinforced ducts. The spring steel helix is completely fabric enclosed for excellent flexibility and crush resistance. Flame retardant to UL-94VO, this hose is ideal for dust collection, air movement, fume control and light material handling.

NP-2/Two-Ply: Is the most widely used product, which will work extremely well in both positive and negative pressure applications. The polyester blend/neoprene double-ply construction is the industry standard for all applications requiring air handling, dust and fume control and light material handling. Two-ply construction offers extreme flexibility and compressibility, combined with excellent crush resistance and tensile strength.

Available Sizes: 1-1/2" - 36" I.D.

Temperature Range: -65°F to 260°F

Stock Length: 25'