

**No. PVCB  
CLEAR PVC POLYESTER BRAID REINFORCED HOSE**



Part Number	Inside Diameter	Outside Diameter	Working Pressure PSI@68°F	Working Pressure PSI@122°F	Standard Length	Weight LB/FT
PVCB-018	1/8"	"	350	200	300'	.04
PVCB-316	3/16"	3/8"	250	150	300'	.04
PVCB-014	1/4"	"	250	150	300'	.06
PVCB-516	5/16"	"	250	135	300'	.08
PVCB-038	3/8"	"	225	125	300'	.09
PVCB-012	1/2"	3/4"	200	100	300'	.13
PVCB-058	5/8"	7/8"	200	100	200'	.18
PVCB-034	3/4"	1"	150	85	200'	.22
PVCB-100	1"		125	75	200'	.30
PVCB-114	1-1/4"	1-5/8"	100	55	100'	.45
PVCB-112	1-1/2"	1-15/16"	100	50	100'	.64
PVCB-200	2"	2-1/2"	75	35	100'	.94

\* **Note:** Working pressure decreases as temperature increases.

**Construction:** Crystal clear PVC reinforced with spiraled polyester cords. Also reinforced with multiple longitudinal polyester cords to reduce elongation under pressure. Cover and tube are compounded from Non-toxic PVC ingredients.

**Features:** Good transparency, smooth bore, chemical resistant, self extinguishing, non-marking.

**Recommended For:** Pneumatic lines, air & water lines, glue lines, air breathing lines, lubrication lines, various machine tools, applications where Poly-Vinyl Chloride is compatible with the media to be conveyed.

**Temperature Range:** +25°F to 150°F

**Lengths:** Standard lengths, also cut and/or coupled to individual customer requirements.

\* **Note:** Also available in FDA &/or USDA approved hose. Please specify on quotation/purchase order.