

**No. PVCW
CLEAR PVC REINFORCED WITH SPRING WIRE**



Part Number	Inside Diameter	Outside Diameter	Working Pressure PSI@68°F	Working Pressure PSI@122°F	Standard Length	Weight LB/FT
PVCW-014	1/4"	1/2"	250	80	100'	.10
PVCW-038	3/8"	5/8"	150	80	100'	.13
PVCW-012	1/2"	13/16"	150	80	100'	.21
PVCW-058	5/8"	1"	150	65	100'	.30
PVCW-034	3/4"	1-1/8"	150	65	100'	.36
PVCW-100	1'	1-3/8"	100	45	100'	.44
PVCW-114	1-1/4"	1-3/4"	100	50	50'	.74
PVCW-112	1-1/2"	2"	100	35	50'	.84
PVCW-200	2"	2-1/2"	100	35	50'	1.12
PVCW-250	2-1/2"	3"	50	30	50'	1.38
PVCW-300	3"		50	30	50'	1.62

* **Note:** Working pressure decreases as temperature increases.

* **Caution:** This product is designed to dissipate static electricity when the metal wire is properly connected to ground, through the fitting and other means.

Construction: Crystal clear PVC reinforced with a spring wire. Compounded from non-toxic PVC ingredients.

Features: Full vacuum rating, anti-kinking, anti-collapsible, chemical resistant, non-toxic, full clear visual flow, smooth tube to reduce material build-up.

Recommended For: Full vacuum lines, air & water supply lines, industrial vacuum pumps, air breathing lines, coolant lines, food and beverage dispensing, deionized water systems, car wash applications, pneumatic parts transfer.

Temperature Range: +25°F to 150°F

Lengths: Standard lengths, also cut and/or coupled to individual customer requirements.

* **Note:** Also available in FDA &/or USDA approved hose. Please specify on quotation/purchase order.