

**No. BDLTB / BDLTC
LOW TEMPERATURE PVC BLOWER DUCT**

Series "BDLTB" Solid Black Color



Series "BDLTC" Clear with Black Helix



Part Number	Inside Diameter	Outside Diameter	Working Pressure PSI@68°F	Working Pressure PSI@104°F	Vacuum In. Hg@68°F	Vacuum In. Hg@104°F	Min. Bend Radius	Weight LB/FT
BDLTB/C-400	4"	4-37/64"	8	4	13	7	3"	.85
BDLTB/C-600	6"	6-5/8"	6	3	7	5	6"	1.34
BDLTB/C-700	7"	7-9/16"	4	2	6	4	7"	1.53
BDLTB/C-800	8"	8-5/8"	4	2	5	3	8"	2.00

Construction: Made of PVC with smooth bore tube which allows full flow and resists material build-up, with corrugated cover. The extreme clarity of series "BDLTC" makes it most suitable for applications where visibility of flow is an important requirement.

Recommended For: General purpose low temperature PVC blower duct. Exposed helix provides for increased flexibility and slides easily for ease of handling.

Temperature: Static condition -20°F to 150°F.

Lengths: Standard 50 ft. for all sizes; and 100 ft. on sizes 4" and 6" ID, also cut and/or coupled to individual client's requirements.

Couplings: KC Nipples, Shank couplings, Cam & Groove, etc.