

GROUND JOINT COUPLINGS



Size	Stem, Wing Nut & Female Spud Part #:	Male Stem Part #:	Wing Nut Part #:	Female Spud Part #:	Male Spud Part #:	Double Spud Part #:	Washer Part #:
1/2"	GJS-050	GMS-050	GWN-050	GFS-050	MS-050	DS-050	GW-050
3/4"	GJS-075	GMS-075	GWN-075	GFS-075	MS-075	DS-075	GW-075
1"	GJS-100	GMS-100	GWN-100	GFS-100	MS-100	DS-100	GW-100
1-1/4"	GJS-125	GMS-125	GWN-125	GFS-125	MS-125	DS-125	GW-125
1-1/2"	GJS-150	GMS-150	GWN-150	GFS-150	MS-150	DS-150	GW-150
2"	GJS-200	GMS-200	GWN-200	GFS-200	MS-200	DS-200	GW-200
2-1/2"	GJS-250	GMS-250	GWN-250	GFS-250	MS-250	DS-250	GW-250
3"	GJS-300	GMS-300	GWN-300	GFS-300	MS-300	DS-300	GW-300
4"	GJS-400	GMS-400	GWN-400	GFS-400	***	***	GW-400

STEAM QUICK DISCONNECT COUPLINGS

Designed exclusively for steam applications, the Socket and Plug are solid brass with stainless steel springs and locking balls. The socket has a large plated steel sleeve especially designed for easier gripping with gloves. Two ethylene propylene O-rings in the Socket provide double protection against leaks. Rated to 100 PSI Gauge Saturated Steam (338°F).

Coupler

Poppet Valve Plug



Part Number	Body Size	Female NPT Size
SQD6-200S	1/4"	1/4"
SQD6-300S	3/8"	3/8"
SQD6-400S	1/2"	1/2"
SQD6-600S	3/4"	3/4"
SQD6-800S	1"	1"

Part Number	Body Size	Female NPT Size
SQD7-200S	1/4"	1/4"
SQD7-300S	3/8"	3/8"
SQD7-400S	1/2"	1/2"
SQD7-600S	3/4"	3/4"
SQD7-800S	1"	1"

Note: Ground joint couplings and the steam quick disconnects are the only couplings recommended for steam service.