

**GROUND JOINT COUPLINGS**



| Size   | Stem, Wing Nut & Female Spud Part #: | Male Stem Part #: | Wing Nut Part #: | Female Spud Part #: | Male Spud Part #: | Double Spud Part #: | Washer Part #: |
|--------|--------------------------------------|-------------------|------------------|---------------------|-------------------|---------------------|----------------|
| 1/2"   | GJS-050                              | GMS-050           | GWN-050          | GFS-050             | MS-050            | DS-050              | GW-050         |
| 3/4"   | GJS-075                              | GMS-075           | GWN-075          | GFS-075             | MS-075            | DS-075              | GW-075         |
| 1"     | GJS-100                              | GMS-100           | GWN-100          | GFS-100             | MS-100            | DS-100              | GW-100         |
| 1-1/4" | GJS-125                              | GMS-125           | GWN-125          | GFS-125             | MS-125            | DS-125              | GW-125         |
| 1-1/2" | GJS-150                              | GMS-150           | GWN-150          | GFS-150             | MS-150            | DS-150              | GW-150         |
| 2"     | GJS-200                              | GMS-200           | GWN-200          | GFS-200             | MS-200            | DS-200              | GW-200         |
| 2-1/2" | GJS-250                              | GMS-250           | GWN-250          | GFS-250             | MS-250            | DS-250              | GW-250         |
| 3"     | GJS-300                              | GMS-300           | GWN-300          | GFS-300             | MS-300            | DS-300              | GW-300         |
| 4"     | GJS-400                              | GMS-400           | GWN-400          | GFS-400             | ***               | ***                 | GW-400         |

**STEAM QUICK DISCONNECT COUPLINGS**

Designed exclusively for steam applications, the Socket and Plug are solid brass with stainless steel springs and locking balls. The socket has a large plated steel sleeve especially designed for easier gripping with gloves. Two ethylene propylene O-rings in the Socket provide double protection against leaks. Rated to 100 PSI Gauge Saturated Steam (338°F).

**Coupler**

**Poppet Valve Plug**



| Part Number | Body Size | Female NPT Size |
|-------------|-----------|-----------------|
| SQD6-200S   | 1/4"      | 1/4"            |
| SQD6-300S   | 3/8"      | 3/8"            |
| SQD6-400S   | 1/2"      | 1/2"            |
| SQD6-600S   | 3/4"      | 3/4"            |
| SQD6-800S   | 1"        | 1"              |

| Part Number | Body Size | Female NPT Size |
|-------------|-----------|-----------------|
| SQD7-200S   | 1/4"      | 1/4"            |
| SQD7-300S   | 3/8"      | 3/8"            |
| SQD7-400S   | 1/2"      | 1/2"            |
| SQD7-600S   | 3/4"      | 3/4"            |
| SQD7-800S   | 1"        | 1"              |

**Note:** Ground joint couplings and the steam quick disconnects are the only couplings recommended for steam service.