

## SAND BLAST COUPLINGS

All sand blast couplings are supplied with screws and gaskets. Installation: 1) Ends of hose must be cut square to fit snug against metal end. 2) Holding hose tight to end of fitting, insert screws and turn in full putting screw 180° from first to insure best centering. 3) After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through. 4) On quick couplings insert safety clips.



### Hose End x Crowfoot

These fittings are designed for use on sand blast hose.

Size	Hose OD	Aluminum Part #:	Brass Part #:	Cast Iron Part #:	Nyglass Part #:
3/4"	1-1/2"	ASB075	BSB075	CISB075	NSB075
1"	1-7/8"	ASB100	BSB100	CISB100	NSB100
1-1/4"	2-5/32"	ASB125	BSB125	CISB125	NSB125
1-1/2"	2-3/8"	ASB150	BSB150	CISB150	NSB150



### Hose End Nozzle Holder

These fittings are designed for use on sand blast hose. Nozzle holders have 1-1/4" NPSM thread

Size	Hose OD	Aluminum Part #:	Brass Part #:	Cast Iron Part #:	Nyglass Part #:
3/4"	1-1/2"	ANH075	BNH075	CINH075	NNH075
1"	1-7/8"	ANH100	BNH100	CINH100	NNH100
1-1/4"	2-5/32"	ANH125	BNH125	CINH125	NNH125
1-1/2"	2-3/8"	ANH150	BNH150	CINH150	NNH150



### Female NPT x Crowfoot

Threaded couplings/adapters x crowfoot.

NPT Size	Hose OD	Aluminum Part #:	Brass Part #:
1-1/4"	1-1/2"	ASC125	BSC125
1-1/2"	1-7/8"	ASC150	BSC150

No. SBG - SBR gaskets for all sand blast couplings.

No. SBCS - 10 x 5/8" Zinc plated phillips head screws for all sand blast couplings.