

**BRASS MARINE & INDUSTRIAL FITTINGS**

**No. 251 - Brass Long Shank Coupling**

Long shank couplings are commonly used on low pressure air or steam hose. The long shanks accommodate two or more clamps for safe sealing of coupling to hose.



Part Number	Shank Size	Thread Size	Thread Type	Nut Type
251-1575NPT	1/2"	3/4"	NPT	Hex
251-1575GHT	1/2"	3/4"	GHT	Hex
251-5875NPT	5/8"	3/4"	NPT	Hex
251-5875GHT	5/8"	3/4"	GHT	Hex
251-075NPT	3/4"	3/4"	NPT	Hex
251-075GHT	3/4"	3/4"	GHT	Hex
251-075GHT	3/4"	3/4"	GHT	Hex
251-100NPT	1"	1"	NPT	Hex
251-125NPT	1-1/4"	1-1/4"	NPT	Hex
251-150NPT	1-1/2"	1-1/2"	NPT	Pin
251-150NST	1-1/2"	1-1/2"	NST	Hex, Pin
251-200NPT	2"	2"	NPT	Pin
251-250NST	2-1/2"	2-1/2"	NST	Hex

**No. 268-BR - Brass Short Shank Coupling**

268-BR short shank couplings are cast of high grade red brass for maximum strength. Recommended when hose is used around salt water, in mines and when a non-sparking coupling is needed.

**Also available with aluminum shank and brass nut, (PN: 268AL-).**



Part Number	Shank Size	Thread Size	Thread Type	Nut Type	IMPA Code
268-1575NPT	1/2"	3/4"	NPT	Hex	--
268-1575GHT	1/2"	3/4"	GHT	Hex	--
268-5875NPT	5/8"	3/4"	NPT	Hex	--
268-5875GHT	5/8"	3/4"	GHT	Hex	--
268-075NPT	3/4"	3/4"	NPT	Hex	--
268-075GHT	3/4"	3/4"	GHT	Hex	--
268-075GHT	3/4"	3/4"	GHT	Hex	--
268-100NPT	1"	1"	NPT	Hex	--
268-125NPT	1-1/4"	1-1/4"	NPT	Hex	--
268-150NPT	1-1/2"	1-1/2"	NPT	Pin	330867
268-150NST	1-1/2"	1-1/2"	NST	Hex, Pin	330865
268-200NPT	2"	2"	NPT	Pin	--
268-250NST	2-1/2"	2-1/2"	NST	Pin	330866
268-300NPT	3"	3"	NPT	Pin	--
268-400NPT	4"	4"	NPT	Pin	--
268-600NPT	6"	6"	NPT	Pin	--