

No. DBC - DOUBLE BOLT CLAMPS

A rugged plated malleable iron two-bolt clamp with machine bolts and hex nuts. Inner surface has dual gripping ridges. Bolt lugs are reinforced to prevent bending out of alignment.



Min. Hose O.D.	Max. Hose O.D.	Part #:
1-1/8"	1-3/16"	DBCJ48
1-3/16"	1-3/8"	DBCJ49
1-7/16"	1-17/32"	DBCJX49
1-5/8"	1-13/16"	DBC DL14
1-3/4"	2-3/64"	DBC DL20
2-7/64"	2-19/64"	DBC DL24
2-5/16"	2-5/8"	DBC DL32
2-1/2"	2-3/4"	DBC DL275
2-3/4"	3-1/16"	DBC DL306
3-1/16"	3-3/8"	DBC DL328
3-1/4"	3-1/2"	DBC DL350
3-1/2"	3-13/16"	DBC400
3-25/32"	4-1/16"	DBC431
4-1/32"	4-9/32"	DBC463

Min. Hose O.D.	Max. Hose O.D.	Part #:
4-1/4"	4-15/16"	DBC525
4-1/2"	5-1/4"	DBC550
5-1/8"	5-11/16"	DBC600
5-11/16"	5-15/16"	DBC639
5-15/16"	6-1/2"	DBC675
6-1/2"	7-9/16"	DBC769
7-9/16"	8-3/16"	DBC818
8-1/4"	8-7/8"	DBC875
8-15/16"	9-7/8"	DBC988
9-15/16"	11-3/8"	DBC1125
11-3/16"	13"	DBC1275
12-3/16"	14"	DBC1360
13-3/16"	15"	DBC1450
15-1/16"	17-1/2"	DBC1700

No. SDBC - SPIRAL DOUBLE BOLT CLAMPS

Spiral Double Bolt Clamps are recommended to be used with convoluted PVC hose, et al. Series "WG". For adequate holding power, a single clamp may be used on each end of 4" size. Two clamps are recommended for each end on sizes 6" ID hose and above.



Hose I.D.	Min. Hose O.D.	Max. Hose O.D.	Part #:
1-1/2"	1-23/32"	2-1/8"	SDBC-150
2"	2-9/32"	2-1/2"	SDBC-200
2-1/2"	2-23/32"	3-1/8"	SDBC-250
3"	3"	2-1/2"	SDBC-300
4"	4"	4-1/2"	SDBC-400
5"	5-3/32"	5-1/2"	SDBC-500
6"	6-1/4"	7"	SDBC-600
8"	8-1/2"	9-1/4"	SDBC-800
10"	10-5/8"	1-1/4"	SDBC-1000