

No. 3100A - SPUN ARAMID FIBER PACKING



Larger sizes available on request.

Description: Spun interlock braid using aramid filaments treated individually with PTFE suspenoid. The packing is also lubricated with a silicon-based compound for quick and easy break-in.

Applications: Centrifugal, rotary and reciprocating pumps, valves.

Service: 3100 is a durable packing able to withstand granular and abrasive applications. It is recommended for service in superheated steam, slurries, petroleum derivatives, solvents, chemicals and liquid gases.

Temperature Limit: to 540°F.

pH Range: 2-12.

Shaft Speed: to 2950 FPM.

**** Note:** Available in plain braided aramid fiber with PTFE lubricant, PN: 3100.

Part #	Size	Ft/Lb.	ISSA #
3100A-180	1/8"	78.0	810565
3100A-316	3/16"	42.0	810566
3100A-140	1/4"	27.0	810567
3100A-516	5/16"	16.0	810568
3100A-380	3/8"	11.0	810569
3100A-716	7/16"	8.5	810571
3100A-120	1/2"	6.4	810572
3100A-916	9/16"	5.2	810573
3100A-580	5/8"	4.2	810574
3100A-340	3/4"	3.0	810576
3100A-780	7/8"	2.1	810578
3100A-100	1"	1.7	810579

No. 3300 - EXPANDED PTFE/GRAPHITE



Larger sizes available on request.

Description: Interbraided PTFE/Graphite fiber, graphite particles encapsulated in an expanded PTFE matrix. Recommended for corrosive services that are suitable for graphite/PTFE.

Applications: Reciprocating and rotary shafts, valve stems.

Temperature Limit: to 540°F.

pH Range: 0-14.

Shaft Speed: to 4900 FPM.

Part #	Size	Ft/Lb.
3300-180	1/8"	87.5
3300-316	3/16"	38.2
3300-140	1/4"	22.2
3300-516	5/16"	15.7
3300-380	3/8"	10.3
3300-716	7/16"	8.1
3300-120	1/2"	5.9
3300-916	9/16"	4.5
3300-580	5/8"	3.7
3300-340	3/4"	2.5
3300-780	7/8"	2.0
3300-100	1"	1.6