

No. 600 - RED RUBBER SHEET



Part #	Size
600-116	1/16"
600-332	3/32"
600-180	1/8"
600-316	3/16"
600-140	1/4"

Description: Remains pliable under service conditions and has low flow under bolting pressures. This compound does not readily creep or blow out under normal temperatures or pressures.

Service: An exceptionally good material for use against hot or cold water, air and low pressure saturated steam, not exceeding 50 PSI.

Color: Red.

Tensile: 400 PSI.

Temperature Limit: -20°F to 180°F.

ASTM: D-2000.

*** Note:** Sheets can be cut to length.

No. 610 - PURE GUM (LIVE) RUBBER SHEET



Part #	Size	ISSA #
610-116	1/16"	811112
610-332	3/32"	811113
610-180	1/8"	811114
610-316	3/16"	811116
610-140	1/4"	811117
610-380	3/8"	811119
610-120	1/2"	811120
610-580	5/8"	811121
610-340	3/4"	811122

Description: Pure vegetable rubber compound for softness and tensile strength. An excellent sealing material for applications involving light bolt pressures or extreme flange irregularities.

Service: Hot or cold water, aqueous solutions (except concentrated Sulfuric acid and Nitric acid).

Color: Tan.

Tensile: 1700 PSI.

Temperature Limit: -20°F up to 140°F.

ASTM: D-2000.

*** Note:** Sheets can be cut to length.