

No. 641 - VEGETABLE FIBER SHEET



Description: Manufactured from tough Vegetable fiber impregnated with a chemical binder to resist the penetration of liquids. It is heavily compressed during manufacture to close tolerances.

Service: Designed especially for use against gasoline, oil, benzene, grease, hot and cold water.

Color: Beige - Brown.

Temperature Limit: 250°F Maximum.

*** Note:** Conforms to government specifications 33-P-22 and HH-P-96.

Part #	Size	ISSA #
641-132	1/32"	811084
641-116	1/16"	811086
641-332	3/32"	811087
641-180	1/8"	811088
641-316	3/16"	--
641-140	1/4"	--

No. 645 - CORK AND NEOPRENE SHEET



Description: The material offers exceptional resiliency and conformability.

Service: Cork/neoprene manufactured sheet material is resistant to oils, fuels, weather and water.

Color: Brown.

Temperature Limit: 275°F Maximum.

Pressure Limit: 300 PSI.

*** Note:** Conforms to government specifications MIL-C-6183A and ASTM F 104 F227000M1.

Part #	Size	ISSA #
645-132	1/32"	811001
645-116	1/16"	811002
645-332	3/32"	811003
645-180	1/8"	811004
645-316	3/16"	--
645-140	1/4"	--