

No. CCS - CLOSED CELL SPONGE RUBBER



Description: Natural rubber closed cell sponge.

Service: Sealing water tight doors. Excellent for insulating sound and vibration, dampening, and shock absorbing.

Color: Black.

Size: 36", additional sizes upon request.

Temperature Limit: -40°F to +160°F.

Tensile: 1500 PSI Minimum

Available in sheet or rubber strips cut to order.

Part #	Size
CCS-180	1/8"
CCS-316	3/16"
CCS-140	1/4"
CCS-380	3/8"
CCS-120	1/2"
CCS-580	5/8"
CCS-340	3/4"
CCS-100	1"

No. WPGT - WOVEN PTFE GASKET TAPE



Description: Woven PTFE yarns in a flat, tube-like construction, which is impregnated with PTFE and can be treated with an inert lubricant (No. WPGT WET) or furnished without the lubricant (No. WPGT DRY)

Service Media: It can handle virtually any chemical service with the exception of molten alkali metals. Commonly used for sealing flanges and vessel tank lids.

Temperature Limit: 500°F

Pressure Limit: 360 PSI

pH Range: 0 - 14, except molten alkali metals.

Part #	Width	Thickness	Ft./Lb.	Thickness	Ft./Lb.
WPGT-120-WET	1/2"	1/8"	20.5	1/4"	--
WPGT-340-WET	3/4"	1/8"	13.5	1/4"	6.7
WPGT-100-WET	1"	1/8"	10.0	1/4"	5.0
WPGT-114-WET	1-1/4"	1/8"	8.0	1/4"	4.0
WPGT-112-WET	1-1/2"	1/8"	7.6	1/4"	3.8
WPGT-200-WET	2"	1/8"	--	1/4"	2.5
WPGT-120-DRY	1/2"	1/8"	18.5	1/4"	--
WPGT-340-DRY	3/4"	1/8"	12.5	1/4"	6.6
WPGT-100-DRY	1"	1/8"	9.4	1/4"	4.7
WPGT-114-DRY	1-1/4"	1/8"	7.4	1/4"	3.7
WPGT-112-DRY	1-1/2"	1/8"	6.1	1/4"	3.1
WPGT-200-DRY	2"	1/8"	--	1/4"	2.3