

No. AMT - TWIN ARCH RUBBER BELLOWS WITH FLOATING FLANGES



Part Number	Size I.D.	Length	Fo	Axial Compression	Axial Elongation	Transverse Movement	Angular Deflection	Weight lbs.
AMT201H	1-1/2"	7"	2.7"	1"	3/4"	1"	30°	6.8
AMT202	2"	7"	3.4"	1"	3/4"	1"	30°	9.0
AMT202H	2-1/2"	7"	4.1"	1"	3/4"	1"	30°	12.3
AMT203	3"	7"	4.5"	1"	3/4"	1"	30°	14.3
AMT204	4"	9"	6.0"	1-1/4"	1"	1-1/4"	30°	20.3
AMT205	5"	9"	7.1"	1-1/4"	1"	1-1/4"	30°	24.5
AMT206	6"	9"	8.2"	1-1/4"	1"	1-1/4"	30°	29.5
AMT208	8"	13"	10.2"	1-1/2"	1"	1-1/2"	30°	42.3
AMT210	10"	13"	12.6"	1-1/2"	1"	1-1/2"	30°	56.6
AMT212	12"	13"	14.5"	1-1/2"	1"	1-1/2"	30°	95.0

Construction: Elastomer neoprene, also available are Butyl, EPDM and Buna-N.

Reinforcement: Synthetic fiber fabric.

Flanges: Carbon steel. May be replaced with ANSI, BS, JIS and DIN standard (drillings), please specify when ordering.

Applicable Fluids: Water, warm water, sea water, weak leaks, alkalies, compressed air, etc..

Operating Pressures: 214 PSI.

Vacuum Rating: Full.

Temperature & Range: 14°F to 220°F.