

**No. AMT - TWIN ARCH RUBBER BELLOWS WITH FLOATING FLANGES**



| Part Number | Size I.D. | Length | Fo    | Axial Compression | Axial Elongation | Transverse Movement | Angular Deflection | Weight lbs. |
|-------------|-----------|--------|-------|-------------------|------------------|---------------------|--------------------|-------------|
| AMT201H     | 1-1/2"    | 7"     | 2.7"  | 1"                | 3/4"             | 1"                  | 30°                | 6.8         |
| AMT202      | 2"        | 7"     | 3.4"  | 1"                | 3/4"             | 1"                  | 30°                | 9.0         |
| AMT202H     | 2-1/2"    | 7"     | 4.1"  | 1"                | 3/4"             | 1"                  | 30°                | 12.3        |
| AMT203      | 3"        | 7"     | 4.5"  | 1"                | 3/4"             | 1"                  | 30°                | 14.3        |
| AMT204      | 4"        | 9"     | 6.0"  | 1-1/4"            | 1"               | 1-1/4"              | 30°                | 20.3        |
| AMT205      | 5"        | 9"     | 7.1"  | 1-1/4"            | 1"               | 1-1/4"              | 30°                | 24.5        |
| AMT206      | 6"        | 9"     | 8.2"  | 1-1/4"            | 1"               | 1-1/4"              | 30°                | 29.5        |
| AMT208      | 8"        | 13"    | 10.2" | 1-1/2"            | 1"               | 1-1/2"              | 30°                | 42.3        |
| AMT210      | 10"       | 13"    | 12.6" | 1-1/2"            | 1"               | 1-1/2"              | 30°                | 56.6        |
| AMT212      | 12"       | 13"    | 14.5" | 1-1/2"            | 1"               | 1-1/2"              | 30°                | 95.0        |

**Construction:** Elastomer neoprene, also available are Butyl, EPDM and Buna-N.

**Reinforcement:** Synthetic fiber fabric.

**Flanges:** Carbon steel. May be replaced with ANSI, BS, JIS and DIN standard (drillings), please specify when ordering.

**Applicable Fluids:** Water, warm water, sea water, weak leaks, alkalies, compressed air, etc..

**Operating Pressures:** 214 PSI.

**Vacuum Rating:** Full.

**Temperature & Range:** 14°F to 220°F.