

VP-STANDARD - Portable tanking washing machine for hire.



Features:

- Portable tank-washing machines for rental hire.
- 4 models: “S”, “V”, “L”, and “OBW”.
- Long term or short term hire.
- Long term reliability.
- Robust and durable.
- Easy to use.
- Repair & maintenance by VP included.
- Easy worldwide exchange facilities.
- Turbine drive - self starting.

Types “S”, “V”, and “L”

- Corrosion resistant bronze.
- Automatic, repeating spherical wash pattern for maximum coverage.
- Can be used on cold or hot wash up to 93°C.
- Suitable for standard wash chemicals.
- Robust and durable.
- Standard machine with 3 nozzles.
- Self drive by integral water turbine.
- Enters standard 318mm deck opening.
- Grease filled gearbox.

Hose Connections: Available with connections to suit. VP standard. BW optional. VP hoses 2 3/8” x 11.5 TPI and also with adapters to suit 2” BSP, 2 1/2” BSP, 2 1/2” x 7 1/2” TPI USA or Storz hose couplings.

Dimensions: 305 x 205 x 320 **Weight:** 21 kgs. (47 lbs.) - complete with carrying handle and storage box.

Multi-level washing gives complete coverage of all difficult-to-reach areas.

Supply Pressure kg/cm ²	Type “S” 3 x 5/16” nozzle			Type “V” 3 x 3/8” nozzles			Type “L” 3 x 1/2” nozzles		
	Flow m ³ /hr	Jet Length-m	Cycle mins.	Flow m ³ /hr	Jet Length-m	Cycle mins.	Flow m ³ /hr	Jet Length-m	Cycle mins.
4	10	5	30	17	7	43	27	9	23
6	13	5	23	21	7	32	33	10	18
8	15	6	18	24	8	26	38	12	16
10	17	7	16	27	9	22	43	14	14
12	19	9	14	29	11	20	47	16	12

Type “OBW”

- Designed for bottom washing operations to remove difficult cargoes.
- Unique oscillating action over narrow wash area.
- Tank bottom washer.
- Supplements other machines to give concentrated wash on tank bottom.
- Downward pointing nozzles direct powerful jets in close pattern to rapidly breakdown sediments.
- Corrosion resistant bronze.

Capacity: 35m³/hr.

Dimensions: 460 x 300mm.

Temperature: Up to 200°F (93°C).

Weight: 29 kgs.