

No. HP - PYREX® HIGH PRESSURE GLASS TUBING

These gage glasses are made from heat-resistant Pyrex® brand tubing. They are most versatile and widely used of all tubular gage glass.



Part Number	Size	Length	Standard Package Quantity	Max. W/P Temp. up to 150°F, no corrosion - PSI	Max. W/P steam boiler service up to 425°F - PSI
HP-1208		8"	6	460	340
HP-1210	1/2" O.D.	10"	6	445	335
HP-1212		12"	6	435	325
HP-1214	+0, -1/32"	14"	6	415	315
HP-1216		16"	6	400	300
HP-1218	Wall	18"	6	385	295
HP-1220	5/64" ±1/64	20"	6	375	285
HP-1224		24"	6	340	270
HP-1230		30"	6	295	**
HP-1236		36"	6	260	**
HP-1248		48"	6	205	**
HP-1260	Max. Length	60"	3	155	**
HP-1272	is 150"	72"	3	110	**
HP-5808		8"	6	435	320
HP-5810	5/8" O.D.	10"	6	420	315
HP-5812		12"	6	410	305
HP-5814	+0 -1/32"	14"	6	390	295
HP-5816		16"	6	375	285
HP-5818	Wall	18"	6	360	280
HP-5820	3/32", ±1/64"	20"	6	350	270
HP-5824		24"	6	320	255
HP-5830		30"	6	280	**
HP-5836		36"	6	245	**
HP-5848		48"	6	195	**
HP-5860	Max. Length	60"	3	150	**
HP-5872	is 150"	72"	3	100	**
HP-3408		8"	6	425	315
HP-3410	3/4" O.D.	10"	6	410	310
HP-3412		12"	6	400	300
HP-3414	+0 -1/32"	14"	6	385	290
HP-3416		16"	6	370	280
HP-3418	Wall	18"	6	355	275
HP-3420	7/64", ±1/64"	20"	6	345	265
HP-3424		24"	6	315	250
HP-3430		30"	6	275	**
HP-3436		36"	6	240	**
HP-3448		48"	6	190	**
HP-3460	Max. Length	60"	3	145	**
HP-3472	is 150"	72"	3	100	**
HP-7808		8"	3	380	
HP-7810	7/8" O.D.	10"	3	370	Not
HP-7812		12"	3	360	recommended
HP-7814	+0, -1/32"	14"	3	350	in this service.
HP-7816		16"	3	340	
HP-7818	Wall	18"	3	335	Not
HP-7820	1/8" ±1/32"	20"	3	330	recommended
HP-7824		24"	3	315	in this service.
HP-7830		30"	3	285	
HP-7836		36"	3	265	Not
HP-7848		48"	3	210	recommended
HP-7860	Max. Length	60"	3	160	in this service.
HP-7872	is 150"	72"	3	110	

* Note: Maximum recommended length is 24".