

No. RL - PYREX® BRAND RED LINE GLASS TUBING

It is easy to spot liquid levels from a distance when using Pyrex® Brand Red Line tubular gage glass. The red stripe on a white background gives a special optical effect which makes the liquid level stand out clearly. Thus the gage can be easily read from across a room. Made from heat-resistant Pyrex® brand tubing.



Part Number	Size	Length	Standard Package Quantity	Max. W/P Temp. up to 150°F, no corrosion - PSI	Max. W/P steam boiler service up to 425°F - PSI
RL-1208		8"	6	390	300
RL-1210	1/2" O.D.	10"	6	370	295
RL-1212		12"	6	360	295
RL-1214	+0, -1/32"	14"	6	345	290
RL-1216		16"	6	335	285
RL-1218	Wall	18"	6	325	280
RL-1220	5/64", ±1/64"	20"	6	310	280
RL-1224		24"	6	280	270
RL-1230		30"	6	250	**
RL-1236		36"	6	215	**
RL-1248		48"	6	175	**
RL-1260		60"	3	135	**
RL-1272	Max. Length	72"	3	100	**
RL-5808		8"	6	370	285
RL-5810	5/8" O.D.	10"	6	345	280
RL-5812		12"	6	335	280
RL-5814	+0, -1/32"	14"	6	325	275
RL-5816		16"	6	315	270
RL-5818	Wall	18"	6	305	265
RL-5820	3/32", ±1/64"	20"	6	290	265
RL-5824		24"	6	265	255
RL-5830		30"	6	235	**
RL-5836		36"	6	205	**
RL-5848		48"	6	165	**
RL-5860		60"	3	125	**
RL-5872	Max. Length	72"	3	90	**
RL-3408		8"	6	360	280
RL-3410	3/4" O.D.	10"	6	340	275
RL-3412		12"	6	330	275
RL-3414	+0, -1/32"	14"	6	320	270
RL-3416		16"	6	310	265
RL-3418	Wall	18"	6	300	260
RL-3420	7/64", ±1/64"	20"	6	285	260
RL-3424		24"	6	260	250
RL-3430		30"	6	230	**
RL-3436		36"	6	200	**
RL-3448		48"	6	160	**
RL-3460		60"	3	125	**
RL-3472	Max. Length	72"	3	90	**
RL-7808		8"	3	315	
RL-7810	7/8" O.D.	10"	3	310	Not recommended
RL-7812		12"	3	305	in this service.
RL-7814	+0, -1/32"	14"	3	300	
RL-7816		16"	3	285	
RL-7818	Wall	18"	3	280	Not recommended
RL-7820	1/8", ±1/32"	20"	3	275	in this service.
RL-7824		24"	3	265	
RL-7830		30"	3	240	
RL-7836		36"	3	225	Not recommended
RL-7848		48"	3	185	in this service.
RL-7860		60"	3	145	
RL-7872	Max. Length	72"	3	100	
RL-1008		8"	3	275	
RL-1010	1" O.D.	10"	3	270	Not recommended
RL-1012		12"	3	265	in this service.
RL-1014	+0, -1/32"	14"	3	260	
RL-1016		16"	3	250	
RL-1018	Wall	18"	3	245	Not recommended
RL-1020	1/8", ±1/32"	20"	3	240	in this service.
RL-1024		24"	3	230	
RL-1030		30"	3	210	
RL-1036		36"	3	195	Not recommended
RL-1048		48"	3	160	in this service.
RL-1060		60"	3	125	
RL-1072	Max. Length	72"	3	90	

* Note: Maximum recommended length is 24".