

**No. DOSD
DOCK / OIL SUCTION & DISCHARGE HOSE**



Part Number	Inside Diameter	Outside Diameter	Bend Radius	Weight LB/FT	Working Pressure-PSI
DOSD-300	3"	4-7/16"	15"	4.17	200
DOSD-400	4"	5-3/16"	16"	6.00	200
DOSD-600	6"	7-1/4"	36"	9.31	200
DOSD-800	8"	9-9/16"	48"	12.09	200
DOSD-1000	10"	11-15/32"	60"	20.05	200
DOSD-1200	12"	13-9/16"	72"	26.45	200

Description: Heavy duty, multi-purpose suction & discharge hose. Designed specifically for transferring petroleum products to and from tankers, barges and storage tanks. Exclusive construction allows for excellent flexibility and handling ease. Rugged all weather cover is resistant to oil, cuts, gouges, scuffs, and ozone attack. Available in smooth or corrugated construction with built-in or swaged end styles. Meets all Coast Guard regulations for Dock/O.S. & D. hose.

Tube: Seamless nitrile blend. Resistant up to 50% aromatics.

Reinforcement: Multiple plies of polyester with helix wire.

Cover: Neoprene.

Temperature & Range: -40°F to 180°F.

Lengths: 100 ft. for sizes up to 8"; 50' for sizes 10" & 12", cut and/or coupled to client's individual requirements.