

## No. 90 - "RAMIE" FLAX PACKING FOR THE MARINE TRADE



Larger sizes available on request.

**Description:** Square braided medium flax fibers paraffin treated and mineral oil lubricated.

**Applications:** General service packings recommended for cold water, cold oil and brine applications. Stern tubes, rudder posts and tail shaft liners and industrial applications where minimal shaft scoring rates are required.

**Service:** This packing has extremely low frictional characteristics where minimal shaft wear is essential. Style 90 is rot resistant and ideal for marine use, handling cold water, brine and cold oils.

**Temperature Limit:** 212°F.

**pH Range:** 6-8.

**Shaft Speed:** to 1200 FPM.

Part #	Size	Ft/Lb.	ISSA #
90-180	1/8"	114.0	810201
90-316	3/16"	57.0	810202
90-140	1/4"	34.0	810203
90-516	5/16"	21.0	810204
90-380	3/8"	16.0	810205
90-716	7/16"	10.0	810206
90-120	1/2"	8.5	810207
90-916	9/16"	6.6	810208
90-580	5/8"	5.4	810209
90-340	3/4"	3.9	810211
90-780	7/8"	3.0	810213
90-100	1"	2.4	810215
90-118	1-1/8"	1.8	
90-114	1-1/4"	1.5	810216
90-112	1-1/2"	1.0	

## No. 90G - LUBRICATED RAMIE FLAX PACKING WITH GRAPHITE



Larger sizes available on request.

**Description:** Square braided medium flax fibers paraffin treated with a petroleum based lubricant and graphite.

**Applications:** General service packings recommended for cold water, salt water, cold oil and brine applications. Stern tubes, rudder posts and tail shaft liners and industrial applications where minimal shaft scoring rates are required.

**Service:** This packing has extremely low frictional characteristics where minimal shaft wear is essential.

**Temperature Limit:** 212°F.

**pH Range:** 6-8.

**Shaft Speed:** to 1200 FPM.

Part #	Size	Ft/Lb.
90G-180	1/8"	93.0
90G-316	3/16"	53.0
90G-140	1/4"	27.0
90G-516	5/16"	20.0
90G-380	3/8"	15.0
90G-716	7/16"	10.0
90G-120	1/2"	8.3
90G-916	9/16"	6.3
90G-580	5/8"	5.7
90G-340	3/4"	3.8
90G-780	7/8"	2.9
90G-100	1"	2.2
90G-118	1-1/8"	1.8
90G-114	1-1/4"	1.4
90G-112	1-1/2"	1.0