

**No. WG  
PVC MULTI-PURPOSE SUCTION HOSE**

Series "WG" Solid Green Color



Part Number	Inside Diameter	Outside Diameter	Working Pressure PSI@68°F	Working Pressure PSI@104°F	Vacuum In. Hg@68°F	Vacuum In. Hg@104°F	Min. Bend Radius	Weight LB/FT
WG-150	1-1/2"	1-7/8"	50	25	Full	28	2	.34
WG-200	2"	2-3/8"	50	25	Full	28	3	.52
WG-300	3"	3-5/8"	45	22	Full	28	6	1.17
WG-400	4"	4-3/4"	35	18	Full	28	8	1.92
WG-600	6"	7"	30	15	28	25	14	3.75

**Construction:** PVC general purpose suction hose. Designed with a convoluted cover for high flexibility and a smooth bore for unrestricted flow. Solid green color.

**Recommended For:** General purpose suction and delivery of fluids, construction and mining, irrigation lines, rock dusting and sanitary vacuuming

**Temperature Range:** -4°F to 150°F.

**Lengths:** Standard 100 ft., also cut and/or coupled to individual client's requirements.

**Couplings:** KC Nipples, Shank couplings, Cam & Groove, etc.

**No. CVT10  
CLEAR VINYL TUBING**



Part Number	ID	OD	Nom. Wall	WP PSI@ 70°F	Std. Lgth	Wt. lb/ft	Part Number	ID	OD	Nom. Wall	WP PSI@ 70°F	Std. Lgth	Wt. lb/ft
CVT-10-18	1/8"	1/4"	1/16"	65	100'	.02	CVT-10-58	5/8"	13/16"	3/32"	35	100'	.12
CVT-10-316	3/16"	1/4"	1/32"	50	100'	.01	CVT-10-581	5/8"	7/8"	1/8"	40	100'	.16
CVT-10-3161	3/16"	5/16"	1/16"	55	100'	.03	CVT-10-34	3/4"	1"	1/8"	35	100'	.19
CVT-10-3162	3/16"	3/8"	3/32"	60	100'	.05	CVT-10-341	3/4"	1-1/8"	3/16"	45	100'	.30
CVT-10-14	1/4"	3/8"	1/16"	55	100'	.04	CVT-10-342	3/4"	1-1/4"	1/4"	40	100'	.43
CVT-10-141	1/4"	7/16"	3/32"	58	100'	.06	CVT-10-78	7/8"	1-1/8"	1/8"	30	100'	.21
CVT-10-142	1/4"	1/2"	1/8"	60	100'	.08	CVT-10-781	7/8"	1-1/4"	3/16"	35	100'	.34
CVT-10-516	5/16"	7/16"	1/16"	50	100'	.04	CVT-10-100	1"	1-1/4"	1/8"	25	100'	.24
CVT-10-5161	5/16"	1/2"	3/32"	55	100'	.07	CVT-10-1001	1"	1-3/8"	3/16"	30	100'	.38
CVT-10-5162	5/16"	9/16"	1/8"	60	100'	.10	CVT-10-1002	1"	1-1/2"	1/4"	35	100'	.54
CVT-10-38	3/8"	1/2"	1/16"	45	100'	.05	CVT-10-114	1-1/4"	1-1/2"	1/8"	20	50'	.30
CVT-10-381	3/8"	9/16"	3/32"	50	100'	.08	CVT-10-1141	1-1/4"	1-5/8"	3/16"	30	50'	.46
CVT-10-382	3/8"	5/8"	1/8"	55	100'	.11	CVT-10-1142	1-1/4"	1-3/4"	1/4"	40	50'	.64
CVT-10-12	1/2"	5/8"	1/16"	30	100'	.06	CVT-10-112	1-1/2"	1-7/8"	3/16"	30	50'	.54
CVT-10-121	1/2"	11/16"	3/32"	40	100'	.10	CVT-10-1121	1-1/2"	2"	1/4"	35	50'	.75
CVT-10-122	1/2"	3/4"	1/8"	45	100'	.14	CVT-10-200	2"	2-1/2"	1/4"	35	50'	.96

\* **Note:** Working pressure decreases as temperature increases.

**Construction:** Non reinforced clear vinyl tubing. Cover and tube are compounded from Non-toxic PVC ingredients.

**Features:** The extreme clarity makes it most suitable for applications where visibility of flow is important. Easy to handle, good transparency, smooth bore, self extinguishing, non-marking.

**Recommended For:** Tubing in laboratories, air & water lines, de-ionized water lines, refrigeration drainage, ice making machines, bottling plants, beverage dispenser units.

**Temperature Range:** +25°F to 150°F

**Lengths:** Standard lengths, also cut and/or coupled to individual customer requirements.

\* **Note:** Also available in FDA &/or USDA approved hose. Please specify on quotation/purchase order.