

**No. NF (NU-FLOW) / VF (VINYLFLOW)  
BLUE PVC LAYFLAT - GENERAL PURPOSE WATER DISCHARGE HOSE**



Part Number	ID	Nom. Wall	WP PSI	Std Lgth	Wt lb/ft
NF-075	53/64"	3/64"	70	300'	.08
NF-100	1-1/16"	3/64"	70	300'	.10
NF-125	1-3/8"	3/64"	70	300'	.13
NF-150	1-39/64"	3/64"	70	300'	.15
NF-200	2-7/64"	3/64"	65	300'	.20
NF-250	2-19/32"	3/64"	60	300'	.28
NF-300	3-3/32"	3/64"	60	300'	.34
NF-400	4-3/32"	1/16"	60	300'	.45
NF-500	5-5/64"	5/64"	40	300'	.70
NF-600	6-9/64"	5/64"	45	300'	.81
NF-800	8-5/32"	3/32"	45	300'	1.10

Part Number	ID	Nom. Wall	WP PSI	Std Lgth	Wt lb/ft
VF-150	1-43/64"	1/16"	80	300'	.16
VF-200	2-11/64"	1/16"	80	300'	.23
VF-250	2-39/64"	5/64"	80	300'	.29
VF-300	3-1/8"	5/64"	70	300'	.39
VF-400	4-1/8"	3/32"	70	300'	.52
VF-500	5-3/64"	3/32"	40	300'	.68
VF-600	6-3/16"	3/32"	50	300'	.86
VF-800	8-11/64"	7/64"	45	100'/300'	1.30
VF-1000	10-1/8"	1/8"	35	100'	1.81
VF-1200	12-1/8"	1/8"	30	100'	1.95
VF-1400	14-1/4"	1/8"	30	100'	2.62
VF-1600	16-9/64"	1/8"	30	100'	3.10

**Construction/Features:** Homogeneous PVC tube and cover to eliminate separation, reinforced with a high tensile polyester yarn spiral wrap. Light weight, tough, economical, smooth tube for low friction loss, coils flat for easy storage, ultraviolet inhibitors to reduce aging.

**Applications:** Drip Irrigation, construction, mining and general water discharge.

**Temperature Range:** 5°F to 170°F.

**Lengths:** Standard lengths, also, cut and/or coupled to individual customer requirements.

**No. IS - IRONSIDES  
RED PVC LAYFLAT - GENERAL PURPOSE WATER DISCHARGE HOSE**



Part Number	ID	Nom. Wall	WP PSI	Std Lgth	Wt lb/ft
IS-150	1-39/64"	3/32"	150	300'	.23
IS-200	2-3/32"	3/32"	150	300'	.32
IS-250	2-37/64"	3/32"	150	300'	.41
IS-300	3-3/32"	7/64"	150	300'	.52
IS-400	4-7/64"	1/8"	125	300'	.76
IS-600	6-5/32"	1/8"	115	300'	1.21
IS-800	8-5/32"	1/8"	70	300'	1.62

**Construction/Features:** Premium quality PVC tube and cover, reinforced with two spiral plies and longitudinal synthetic cords. Excellent as a portable hydrant or relay supply line hose, may be coiled or racked when wet, resists kinking and twisting, high working pressure and high ozone resistance.

**Applications:** Agricultural, quarry, irrigation, construction, mining and industrial applications for general water discharge.

**Temperature Range:** 5°F to 170°F.

**Lengths:** Standard lengths, also cut and/or coupled to individual customer requirements.