

No. 615 - CLOTH INSERTED SBR SHEET



| Part # | Size |
|---------|-------|
| 615-132 | 1/32" |
| 615-116 | 1/16" |
| 615-332 | 3/32" |
| 615-180 | 1/8" |
| 615-316 | 3/16" |
| 615-140 | 1/4" |

Description: Manufactured from high quality fabric and rubber compounds for service where ordinary rubber gaskets may creep.

Service: Hot or cold water, air, gas, low pressure steam and hydraulic equipment service. For general gasket use where movement in service, bolts, clamps, and pressures require reinforced rubber sheet.

Color: Black.

Durometer: 70.

Tensile: 450 PSI.

Elongation: 200%.

Temperature Limit: -20°F to 200°F.

ASTM: D-2000.

* **Note:** Sheets can be cut to length.

No. 624N - CLOTH INSERTED BUNA-N SHEET



| Part # | Size |
|----------|-------|
| 624N-132 | 1/32" |
| 624N-116 | 1/16" |
| 624N-332 | 3/32" |
| 624N-180 | 1/8" |
| 624N-316 | 3/16" |
| 624N-140 | 1/4" |

Description: Manufactured from high quality fabric and Buna-N Rubber is a copolymer of acrylonitrile and butadiene.

Service: This sheet has excellent resistance to most petroleum oils and greases, gasoline, alcohols, L-P gases, fuels oils and many other fluids. It has good abrasion resistance. Used where neoprene compounds tend to swell.

Color: Black.

Durometer: 65.

Tensile: 700 PSI.

Temperature Limit: -20°F to 200°F.

ASTM: D-2000.

* **Note:** Sheets can be cut to length.